SAFETY DATA SHEET

MCL-Remover

Prepared to OSHA, ANSI, NOHSC, WHMIS, 1002/58 & 1272/2008/EC Standards | SDS Revision: 1.0

SDS Revision Date: 10/4/2018

	1. PRODUCT INDENTIFICATION
1.1	Product Name:
	LIGHT ELEGANCE LEpro Remover
1.2	Chemical Name:
	Acetone
1.3	Synonyms:
	NA
1.4	Trade Names:
	none
1.5	Product Use:
	PROFESSIONAL USE ONLY
1.6	Manufacturer's Name:
	MCCONNELL LABS, INC.
1.7	Manufacturer's Adress:
	406 SW UMATILLA AVE, REDMOND, OR 97756 USA
1.8	Emergency Phone:
	CHEMTREC: +1 703 527 3887 / +1 800 424 9300 (CCN 696869)
1.9	Business Phone / Fax:

2. HAZARD INDENTIFICATION

Hazard Identification: 2.1

+1 541 526 1417 / +1 541 526 1418

This product is classified as a HAZARDOUS SUBSTANCE and as a DANGEROUS GOOD according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). WARNING! H225 - Highly Flammable, H319 - Causes serious eye irritation, H336 - May cause drowsiness or dizziness, P210 - Keep away from heat, hot surfaces, open flames, sparks - No Smoking, P233 - Keep container tingtly closed, P240 - Ground/bond container and receiving equipment, P241 - Use Explosion-proof electrical, lighting, ventilating equipment, P242 - Use only non-sparking tools, P243 - Take precautionary measures against static discharge, P261 - Avoid breathing mist, spray or vapors, P264 - Wash exposed skin thoroughly after handling, P271 -Was only outdoors or in a well-ventilated area, P280 - Wear eye protection, face protection, protective clothing, protective gloves, P303 + P361 + P353 - If on skin or hair: remove/take-off immediately all contaiminated clothing. Rinse skin with water/shower. P304 + P340 - If inhaled: remove victim to fresh air and kep at rest in a position comfortable for breathing, P305+P351+P338 - If in eyes" Rinse cautiously for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. P312 - Call poison center or doctor/physician if you feel unwell. P337+P313 - If eye irritation persists, get immediate medical attention, P370+P378 - In case of fire: use dry chemical powder, alcohol resistant foam, carbon dioxide (CO2) to extinguish, P403+P223 - Store in a well ventilated place. Keep tightly closed, P405 - Sto locked up, P501 -Dispose of contents/container to comply with local, state and federal regulations, P235 - Keep cool.





Inhalation: YES Absorption: YES Ingestion: YES

Effects of Exposure: 2.3

> INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervouse system depression.

EYES & SKIN: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflamation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal

burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to the skin, especially after prolonged contact. The product can cause allergic skin reactions

la a rachae walte darmatitie) unon nrolongad or ranaatad avneoura

INHALATION: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms

of overexposure can include coughing, wheezing, nasal congestion and difficulty breathing. Inhalation of concentrated vaors can cause central nervous system depression (e.g., drowsiness, headaches, nausea). Odor may give some warning of

exposure but odor fatigue may occur.

2.4 Symptoms of Overexposure:

Symptoms of skin overexposure may include redness, itiching and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, deratitis) upon prolonged or repeated exposure,

Acute Health Effects:

Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and

2.6 Chronic Health Effects:

The material may cause an allergic reaction for some sensitive individuals.

Target Organs:

Eyes, skin

		3. COMI	POSITION	& INGRE	DIENT	INF	ORM	ATIO	N				
					EXPO:	SURE L	IMITS I	N AIR (mg/m3	3)			
					AC	GIH		NOHSO			OSHA		
					pp	m		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
ACETONE	67-64-1	AL3150000	200-662-2	98-100	500	750	250	1000	NF	1000	NA	2500	
							•		•			•	
CI 16035 (Red 40)	25956-17-6	VV8760000	247-368-0	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA	

4. FIRST AID MEASURES

4.1 First Aid:

INGESTION: If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient

is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the

amount of the substance that was swallowed.

SKIN & EYES: If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s)

to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water followed by a thorough washing of the affected area with plenty of soak and waster. Remove all contaminated clothing including footwear and wash thoroughly

hafora rausa. If irritation radnass or swalling narsists consult a physician immadiataly

INHALATION: Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention.

4.2 Medical Conditions Aggravated by Exposure:

Pre-existing dermatitis, other skin conditions and disorders of the target organs (eyes, skin)

	5. FIREFIGHTING MEASURES	3 of 8
5.1	Flashpoint & Method:	
	-20 °C (-4 °F) CC	
5.2	Autoignition Temperature: 456 °C (869) °F	
5.3	Flammability Limits: Lower Explosive Limit (LEL): NA Upper Explosive Limit (UEL): NA	
5.4	Fire & Explosion Hazards:	
	This product is flammable. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO,	
	CO2 and Nox)	
5.5	Extinguishing Methods:	
	Water, Foam, CO2, Dry Chemical	
5.6	Fire Fighting Procedures:	
	First responders should wear eye protection. Structural fire fighters must wear full protective equipment and	
	MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains,	
	bodies of water or other enviormentally sensitive reas. If necessary, rinse contaminated equipment with soapy water	
	before returning to service.	

6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., ,1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., >1 gallon [3.785 liters]) deny entery to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of

7. HANDLING AND STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a maintaining after washing. Do not cost drink or smoke while bandling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!

7.3 Special Precautions:

Do not store where temperatures can exceed 50 ℃ (122 T).

	8. E	XPOSURE CONTROLS & PERSONAL PROTECTION	4		
8.1 Ventilation & Engineering Controls: Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate decontaimination					
8.2	Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable			
8.3	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses nose a special hazard: soft lenses may absorb and concentrate irritants.			
8.4	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785]) wear nitrile or improvious gloves			
8.5	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.			

	9. PHYSICAL & CHEMICAL PROPERTIES					
9.1	Density:	0.79 g/ml				
9.2	Boiling Point:	56.5 °C (133 °F)				
9.3	Melting Point:	-95 °C (-139 °F)				
9.4	Evaporation Rate:	7.7 (n-butyl acetate = 1.0)				
9.5	Vapor Pressure:	400 @ 39.5 °C				
9.6	Appearance & Color:	Clear liquid				
9.7	Odor Threashold:	NE				
9.8	Solubility:	soluble in water				
9.9	pH:	NA				
9.1	Viscosity:	approximately 5 cps				
9.1	Flash Point:	-20 °C (-4 °F) CC				
9.1	Other Information:	NA				

10. STABILITY & REACTIVITY

10 Stability:

Relatively stable under ambient conditions when stored properly.

10 Hazardous Decomposition Products:

If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon and nitrogen).

10 Hazardous Polymerization:

Will not occur.

10 Conditions to Avoid:

Exposure or contact to extreme temperatures, incompatable chemicals, strong light sources, sparks and flame.

11 Incompatable Substances:

Strong oxidizers, peroxides, strong acids or alkalis.

12. ECOLOGICAL INFORMATION

12 Environmental Stability:

This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. Butyl Acetate: Koc = 1.82. Water Solubility: 120 parts H₂O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization and biodegredation. This compound's half life is 6.1 hours.

12 Effects on Plants & Animals:

There is no specific data availble for this product on plant life.

12 Effects on Aquatic Life:

There is no specific data availble for this product on aquatic life.

13. DISPOSAL CONSIDERATIONS

13 Waste Disposal:

Dispose inaccordance with local, state and Federal waste laws.

13 Special Considerations:

This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastics is safer for the environment and is more easily handled for disposal according to local, state and Federal regulations.

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR. IATA/ICAO. IMDG. SCT. ADR and the CTDGR.

14 49 CFR (GRD):

CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) - UNTIL 12/31/2020

UN1993. FLAMMABLE LIQUID. N.O.S. (ACETONE). 3. II. LTD QTY (IP VOL ≤ 1.0 L)

14 | IATA (AIR):

ID8000, CONSUMER COMMODITY, 9 (IP VOL \leq 0.5 L)

UN1993, FLAMMABLE LIQUID, N.O.S. (ACETONE), 3, II, LTD QTY (IP VOL ≤ 1.0 L)

14 IMDG (OCN):

UN1993, FLAMMABLE LIQUID, N.O.S. (ACETONE). 3, II, LTD QTY (IP VOL ≤ 1.0 L)

14 TDGR (Canadian GND):

MARK PACKAGE "LIMITED QUANTITY" OR "QUANTITE LIMUTEE" OR "LTD QTY" OR "QUANT LTEE" (IP VOL ≤ 1.0 L)

UN1170. ACETONE SOLUTION. 3. II. LTD OTY (IP VOL > 1.0 L)

15 ADR/RID (EU):

UN1993, FLAMMABLE LIQUID, N.O.S. (ACETONE). 3, II, LTD QTY (IP VOL ≤ 1.0 L)

15 MEXICO (SCT):

UN1193 LIQUIDO INFLAMABLES, N.E.P. (ACETONA), 3, II, CANTIDAD LIMITADA (IP VOL ≤ 1.0 L)

15 ADGR (AUS):

UN1993, FLAMMABLE LIQUID, N.O.S. (ACETONE). 3, II, LTD QTY (IP VOL ≤ 1.0 L)



15. REGULATORY INFORMATION

15 SARA Reporting:

NA

15 SARA Threshold Planning Quantity:

NA

15 TSCA Inventory Status:

All components of this product are listed in the TSCA Inventory or are exempt

15 CERCLA Reportable Quantity (RQ):

ACETONE: 5,0000 lbs (2,270 kg)

16 Other Federal Requirements:

This products complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).

16 Other Canadian Regulations:

This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are on the Priorities Substances List.





16 State Regulatory Information:

Butyl Acetate is listed on the following state criteria list(s): Deleware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersery Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposure Limits for Air Contaminants (WA).

No other ingredients in this producd, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists:
California Proposition 65 (CA), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous
Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances list, (MN), New Jersey Right-to-Know List (NJ),
new Yord Hazardous Substances List (NY), Pennsylvania Right-to-Know list (PA), Washington Permissible Exposures List (WA), Wisconsin

16 67/548/EEC (European Union), Australian NOHSC:2011 (2003), and GHS Requirements:

The primary cononents of this product are not listed in Annex 1 of EU Directive 67/548/EEC.

Butyl Acetate: Flammable (F). Harmful (Xi).

Risk Phrases (R): 11-36/37/38 - Highly Flammable. Irritating to eyes, skin and respiratory system. Safety Phrases (S): 2-23-29 - Keep out of reach of Children. Do not breath gas, fumes, vapor or spray. Do not empty into drains. Keep away from sources of ignition - No Smoking. Avoid contact with skin and eyes, rinse immediately with plenty of water and seek





16. OTHER INFORMATION

16 Other Information:

WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. Avoid breathing fume, gas, mist, vapors, spray. Wear potective gloves and eye/face protection. IF ON SKIN - Wash with soap and water. IF IN EYES - Rinse continuously with water for several minutes.

Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - get medical advice/attention. Do not take internally. Keep away from heat and open flame. KEEP OUT OF THE REACH OF CHILDREN.

16 Terms & Definitions:

Please see last page of this SDS.

16 Disclaimer:

This Safety Data Sheet (SDS) is offered persuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other governement regulations must be reviewed for applicability to this product. To the best of McConnell Labs' knowledge, the information contained herein is reliable and accurate as of the date it was prepared; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to sonsult the latest edition.

16 Prepared for: McConnell Labs, Inc. 406 SW Umatilla Ave Redmond, OR 97756 USA Tel: +1 541 526 1417 Fax: +1 541 526 1418



17 Prepared by: McConnell Labs, Inc. 406 SW Umatilla Ave Redmond, OR 97756 USA

Tel: +1 541 526 1417 Fax: +1 541 526 1418



DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number
--

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists				
TLV	TLV Threshold Limit Value				
OSHA U.S. Occupational Safety and Health Administration					
PEL	Permissible Exposure Limit				
IDLH	Immediately Dangerous to Life and Health				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard			
1 Slight Hazard				
2	Moderate Hazard			
3	Severe Hazard			
4	Extreme Hazard			



PERSONAL PROTECTION RATINGS:

Α		
В	The second second	
С	The second second	
D		
E		
F		





Full Face Respirator





















a Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		
ACD	Acidic		
ALK	Alkaline		
COR	Corrosive		
₩	Use No Water		
ОХ	Oxidizer		
TREFOIL	Radioactive		
TREFOIL	Radioactive		



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
	S
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TCo, LCio, & LCo	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	J.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NDSL	Canadian Non-Domestic Substance List					
PSL	SL Canadian Priority Substances List					
TSCA	A U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(*)	(2)	②	(T)	®		(R)
Class A	lass A Class B Class C		Class D1	Class D2	Class D3	Class E	Class F
Compressed	npressed Flammable Oxidizin		Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

	C E F		*			×	×	
С			N	0	Т	Xi	Xn	
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful	

CLP/GHS (1272/2008/EC) PICTOGRAMS:

				A LANGE OF THE PARTY OF THE PAR		\frac{\dagger}{\cdot}		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment